

STRADA-FT

Forward throw beam for area lighting optimized for XP-G and XP-E

SPECIFICATION:

Dimensions 19.6 x 15.5 mm

Height 8.2 mm

Fastening glue, pin, screw

ROHS compliant yes 1



MATERIALS:

ComponentTypeMaterialColourFinishSTRADA-FTSingle lensPMMAclear

ORDERING INFORMATION:

Component


C12049_STRADA-FT

» Box size: 480 x 280 x 300 mm

Qty in box MOQ MPQ Box weight (kg)

2880 288 144 5.6






See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):


CREE . LED


LED XB-D
FWHM / FWTM Asymmetric
Efficiency 87 %
LEDs/each optic 1
Light colour White
Required components:



CREE - LED


LED XP-E
FWHM / FWTM Asymmetric
Efficiency 92 %
LEDs/each optic 1
Light colour White
Required components:





CREE - LED

LED XP-G
FWHM / FWTM Asymmetric
Efficiency 88 %
LEDs/each optic 1
Light colour White
Required components:



DESCRIPTION LUMILEDS

LED LUXEON A
FWHM / FWTM Asymmetric
Efficiency 87 %
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (MEASURED):



LED LUXEON Rebel
FWHM / FWTM Asymmetric
Efficiency 92 %
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rebel ES
FWHM / FWTM Asymmetric
Efficiency 92 %
LEDs/each optic 1
Light colour White
Required components:



WNICHIA

LED NCSxx19A
FWHM / FWTM Asymmetric
Efficiency 92 %
LEDs/each optic 1
Light colour White
Required components:

WNICHIA


LEDNVSxx19AFWHM / FWTMAsymmetricEfficiency92 %LEDs/each optic1Light colourWhiteRequired components:



OPTICAL RESULTS (MEASURED):


OSRAM


OSLON SSL 150 LED FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic Light colour White Required components:



OSRAM Opto Semiconductors


LED OSLON SSL 80 FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic 1 White Light colour Required components:





LED

FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic Light colour White Required components:



SHARP

LED Double Dome (GM2BB)

FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic White Light colour Required components:




OPTICAL RESULTS (SIMULATED):



LED LUXEON 3030 2D (Square LES)

FWHM / FWTM Asymmetric
Efficiency 95 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PRODUCT DATASHEET C12049_STRADA-FT

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy