


READERS WITH TRICOLOR LED

CZ-3-M12 ATENA (xxx)



Can work with any access control device,


Plastic casing with an M12 thread

Good solution for temperature and humidity loggers

Probe with tricolour RGB-LED, standard wire - 40 cm

Possibility to obtain 6 colours

Will work in Touch and Hold mode.



WIRES	
	DATA
	GND
	RED LED
	BLUE LED
	GREEN LED
	COMMON LEAD

Absolute Maximum Ratings at TA=25°C

Parameter	Blue	Hyper Red	Green	Units
Power dissipation	120	75	123	mW
DC Forward Current	30	30	30	mA
Peak Forward Current [1]	150	185	150	mA
Reverse Voltage	5			V
Operating Temperature	-40°C To +85°C			
Storage Temperature	-40°C To +85°C			

Notes:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.

5. Casing	Plastic
6. Ring material	Ferrite steel + Cu + Ni + Cr+3
7. Signal joint material	Brass + Ni +Cr+3
8. Cable	6*0,14mm ²
9. Fastening method	M20x1 screw
10. LED Kingbright	KPB-3025SURKCGKC
11. Work enviroment	Residential, commercial and lightly industrial
12. Working temperature	-40 °C do +85 °C
13. Humidity	Up to 70%

DEMIURG W.WOJTASIK, R.WROŃSKA WOJTASIK, T.WOJTASIK s.c.

ul. Pustynna 66

93-479 Łódź

tel./fax: 042 636 70 70