

## Specification Sheet

Part Number: PBM0C2



Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

<b>Article Number</b>	151-00228
<b>Type</b>	PBM
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.</li><li>• The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.
<b>Short Description</b>	Push-Button Cable Tie Mount, .25" Hole Dia, .12" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

**Global Part Name**

PBM-PA66-BK

**Width W (Imperial)**

0.26

**Width W (Metric)**

6.6

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.40

**Height H (Metric)**

10.20

**Cable Tie Width Max (Imperial)**

0.2

**Cable Tie Width Max (Metric)**

5.0

**Panel Thickness Max(Imperial)**

0.12

**Panel Thickness Max (Metric)**

3.0

**Mounting Hole Diameter D (Imperial)**

0.25 - 0.29

**Mounting Hole Diameter D (Metric)**

6.25 - 6.55 mm

**Mounting Hole Diameter D Min (Imperial)**

0.25

**Mounting Hole Diameter D Max (Imperial)**

0.29

**Mounting Hole Diameter D Max (Metric)**

6.55

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988