



PANDUIT PART NO.	BUNDLE DIA.		A	B	C	D	E	F	G	H	J	K	MAX. PANEL THICKNESS	MIN. LOOP TENSILE	CROSS SECTION	WEIGHT
	MIN. in (mm)	MAX. in (mm)														
PLWP50SE	.12 (3)	1.97 (50)	.05 (1.3)	.19 (4.8)	.46 (11.7)	.22 (5.6)	.32 (8.1)	8.2 (208.3)	.74 (18.8)	.266 (6.8)	1.3 (33)	.30 (7.6)	.118 (3.0)	50 (222)	STANDARD	.42 (191)

NOTES:

1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND PART COLOR.

											DIMENSIONS IN PARENTHESIS ARE IN METRIC UNITS							
											PANDUIT CORP. TINLEY PARK, ILLINOIS							
											WINGED PUSH MOUNT CABLE TIE WITH CONVOLUTED TUBING BUMP TO PREVENT LATERAL MOVEMENT PLWP30,50SE							
											UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ±.1(2.5) (.XXX) ±.020(.51) (.XX) ±.02(.5) ANGLES ± ---				UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.			
											DRAWN BY SO		MAT'L: HEAT STABILIZED NYLON 6.6 BLACK (-30)				SCALE NONE	
11	10/28/04	JABO	CHANGED FORMAT FOR CONSISTENCY SEE ECN FOR DETAILS							26334	11	DATE 2-11-91		DRAWING NO. SS-26334		DWG SIZE A		
REV	DATE	BY	CHK	DESCRIPTION					ECN - R	CUST	SUP	CHK'D HVP		DRAWING NO. SS-26334		DWG SIZE A		