


## T491W227K004ZT

Obsolete

B45192E, Tantalum, MnO2 Tantalum, 220 uF, 10%, 4 VDC, SMD, Molded, Low Profile, 7343, Height Max = 1.5mm



General Information		
Series	B45192E	
Dielectric	MnO2 Tantalum	
Style	SMD Chip	
Description	SMD, Molded, Low Profile	
Features	Low Profile	
RoHS	Yes	
Termination	Tin	
AEC-Q200	No	
Notes	Obsolete. Old Part Number [Obsolete] Was B45192E0227K409.	

Dimensions		
Footprint	7343	
L	7.3mm +/-0.3mm	
W	4.3mm +/-0.3mm	
Н	1.5mm MAX	
S	1.3mm +/-0.3mm	
F	2.4mm +/-0.1mm	
K	1.3mm TYP	

Specifications	
Capacitance	220 uF
Capacitance Tolerance	10%
Voltage DC	4 VDC (85C), 2.68 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	8%
Failure Rate	N/A
Leakage Current	8.8 uA

Packaging Specifications	
Packaging	T&R, 178mm
Packaging Quantity	1250

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.