



1





THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

Ľ


J


COMPLIANT

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POI STEEL, NICKEL PLATE COPPER ALLOY, 30µ (	ED
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT	
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC		0

COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/2019		
		CHECKED:	DATE:		
EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
		DRAWING NUMBER: 630-3WK	3640-1N5	ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-3WK	3640-1N5	1	





.XX ±0.13

.XXX ±0.05

INSU DIEL WITHSTANDING VOLTAGE:

1000V AC rms

