	- m		0	₿ >		
ω	I		LAYOUT SHOWN AS EXA	MPLE		;
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		2
-Durability : 500 Mating cycles		FR Not Listed PN: 8D511W04PEL				4
-Delivered without Souriau contacts						
-Temperature Range <u>-</u> -65°C to +175°C -Salt Spray : 500 hours		A 17-10-2016	First Release			
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	,
	TITLE     Aluminium Plug 8D series			_		
		SCALE				
ASIC SERIES: 8D 5 - 11 W SHELL TYPE : Plug with RFI Shielding	04 P E L Delivered W/O Contact		General linear Tolerances:	NPRDS / PROJECT <b>859</b>		
CONTACT TYPE : Standard Crimp Contact	ORIENTATION :			This document is the pro	operty of	
SHELL SIZE : 11	CONTACT TYPE : PIN(500 Matings	- SOURIAU	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission			
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-0	-	SOURIAU D		SHEET	
		- A3	8D511W04		1/2	

		۵	г П	m		0
		Contact Layout				
4	×	$ \begin{array}{c}                                     $				
	Conta positi ID A B C C D Shell Arrangement no. cont size no. 11 -4 4	X-axis (mm)         Y-axis (mm)           +.065 (1.65)         +.065 (1.65)           +.065 (1.65)        065 (1.65)          065 (1.65)        065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)          065 (1.65)         +.065 (1.65)	]			
ى			-			
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D511V
					A 17-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:
					SCALE	Alumir
<b>-</b>					NA	General linear Tolerances: ±
					SOURIA	
					FORMAT A3	SOURIAU 8D511W
	Н	G	F	E	D	C

Φ			A			
					4	
					3	
any non-confo which does no						
r of the Parties dation, technic	s or by a th	ird party				
ntry J R		& Control List Listed			2	
W04PEI	L					
	0.10			MOD N°		
CUSTOMER DRAWING						
iinium Plug 8D series						
r	NPRDS / PROJECT					
859           This document is the property of						
.COM it must not be reproduced or communicated without permission						
U DRG I	٧°			SHEET		
V04PEL-	·С			2/2		
В			А			