

## A70GT4470AA00K

Aliases (70GT4470AA00K)

A70, Film, Metallized Polypropylene, General Purpose, 4.7 uF, 10%, 90 VAC, 160 VDC, 85°C

## FRONT VIEW

## **SIDE VIEW**



Click here for the 3D model.

Dimensions	
D	17mm MAX
L	33mm MAX
LL	38mm MIN
F	1mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	200

General Information		
Series	A70	
Dielectric	Metallized Polypropylene	
Style	Axial	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	5.4 g	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C. maxK0 = 320.	

Specifications	
Capacitance	4.7 uF
Capacitance Tolerance	10%
Voltage AC	90 VAC
Voltage DC	160 VDC, 120 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.06% 1kHz
Insulation Resistance	6.383 GOhms
Max dV/dt	1V/us
Inductance	33 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.