PRODUCT DATASHEET CP17570_YASMEEN-50-W-B-WHT

YASMEEN-50-W-B-WHT

~36° spot beam. Assembly with holder B compatible with Ø35 mm BJB and B+W connectors. White version.

SPECIFICATION:

Dimensions Ø 49.9 mm Height 30.5 mm **ROHS** compliant yes 🕕



MATERIALS:


Component	Туре	Material	Colour	Finish
YASMEEN-50-W	Single lens	PMMA	clear	
YASMEEN-50-HLD-B-WHT	Holder	PC	white	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP17570_YASMEEN-50-W-B-WHT	Single lens	252	112	28	9.2
» Box size: 476 x 273 x 305 mm					



PRODUCT DATASHEET CP17570_YASMEEN-50-W-B-WHT



See also our general installation guide: www.ledil.com/installation_guide

2/4

PRODUCT DATASHEET CP17570_YASMEEN-50-W-B-WHT

OPTICAL RESULTS (SIMULATED):




LED V10 Gen 8 FWHM / FWTM 36.0° / 58.0°

Efficiency 92 %

Peak intensity 2.3 cd/lm LEDs/each optic 1

Light colour White Required components:

BJB: 47.360.1020




CITIZEN

LED CLL02x/CLU02x (LES10)

FWHM / FWTM 36.0° / 56.0° Efficiency 93 % Peak intensity 2.4 cd/lm

LEDs/each optic 1 Light colour White

Required components: BJB: 47.360.1020




CITIZEN

LED CLU700/701/702/703

FWHM / FWTM 37.0° / 54.0°
Efficiency 94 %
Peak intensity 2.4 cd/lm

LEDs/each optic 1
Light colour White
Required components:



CREE & LED

BJB: 47.360.1020


 LED
 CMU10xx

 FWHM / FWTM
 36.0° / 56.0°

 Efficiency
 92 %

Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White

Required components: BJB: 47.360.1020





PRODUCT DATASHEET CP17570_YASMEEN-50-W-B-WHT

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDIL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy