

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	03JUL2015	DL	CW
	B	ECR-20-014876	26JUL2021	WQR	CW

120
104
43
27

4X M3 THREAD
4X M3 螺纹孔

SCALE 1:2

130
108
35
32

4- \varnothing 4.4

PANNEL CUT OUT

138
29.8

20.4

NOTES:
1. TECHNICAL CHARACTERISTICS:
BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
SURFACE TREATMENT: POWDER-COATED, GRAY
DEGREE OF PROTECTION: IP65 (MATED)

注释:
1. 技术参数:
主体材料: 铝合金
表面处理: 粉末喷涂, 灰色
防护等级: IP65(配合)

142.2
130
45.7
32

4- \varnothing 4.4

T1520240000-000	H24B-AG-RO
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
	ANGLES ±-
	FINISH ±-
MATERIAL	
TBD	-
-	-

DWN	03JUL2015
DAVID LI	
CHK	03JUL2015
CHRIS WANG	
APVD	03JUL2015
XU XIANG	
PRODUCT SPEC	108-137013
APPLICATION SPEC	114-137013
WEIGHT	-
CUSTOMER DRAWING	

TE Connectivity		NAME		RESTRICTED TO
		H24B-AG-RO		
SIZE	CAGE CODE	DRAWING NO		
A3	-	©-T1520240000000		
SCALE		SHEET	OF	REV
1:1		1	1	B

1470-19 (3/13)