

## Specification Sheet

Part Number: 156-01338



Clips offer an easy securing option when cable ties can't be used.

Clips are reusable, making relocation or adjustments simple.

Clips can be attached to the panel prior to installing the pipe or hose.

Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

All-in-one bundling and mounting solution reduces costs.

1-Pc Cable Ties with Pipe Clip, 10-14mm, PA66HIRHS, Black, 500/pkg

|                     |   |
|---------------------|---|
| Article Number      | 156-01338   |
| Type                | T50SMVCOC10-14  |
| Color               | Black (BK)  |
| Quantity Per        | bag   |
| Product Description | HellermannTyton's 1-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners. |
| Short Description   | 1-Pc Cable Ties with Pipe Clip, 10-14mm, PA66HIRHS, Black, 500/pkg  |

|                                     |   |
|-------------------------------------|---|
| Global Part Name                    | T50SMVCOC10-14-PA66HS/PA66HIRHS-BK  |
| Minimum Tensile Strength (Imperial) | 50.0  |
| Minimum Tensile Strength (Metric)   | 222   |
| Length L (Imperial)                 | 8.3   |
| Length L (Metric)                   | 210.0   |
| Fixation Method                     | Omega Clips   |
| Identification Plate Position       | none  |
| Width W (Imperial)                  | 0.19  |
| Width W (Metric)                    | 4.7   |
| Bundle Diameter Min (Imperial)      | 0.08  |
| Bundle Diameter Min (Metric)        | 2.0   |
| Bundle Diameter Max (Imperial)      | 2.0   |
| Bundle Diameter Max (Metric)        | 50.0  |
| Material                            | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |

|                             |  |
|-----------------------------|--|
| Material Shortcut           | PA66HS PA66HIRHS                       |
| Material Cable Tie          | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability                | UL 94 HB                               |
| Operating Temperature       | -40°F to +221°F (-40°C to +105°C)      |
| ROHS Compliant              | Yes                                    |
| Package Quantity (Imperial) | 500                                    |
| Package Quantity (Metric)   | 500                                    |
| Customs Number              | 3926909988                             |

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)