




.XX ±0.13 .XXX ±0.05 Q

_	
	ORI








NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED



	75Ω (IMPEDANCE)	
(IF PRESENT) SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
	5000MO min	


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:


 $5000M\Omega$ min.

-55°C ~ 125°C

1000V AC rms



		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
COMBINATIO	COMBINATION D-SUB		DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, ONTARIO CANADA	CUFUG TORONTO, ONTARIO CANADA MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 629-17W2	2640-7TD	ISSUE
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-17W2	2640-7TD	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



