




UDSK28-22MM-3/4"-F

Ruland UDSK28-22MM-3/4"-F, 22mm x 3/4" Double Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 1.745" (44.3mm) OD, 7.750" (196.9mm) Length





Description

Ruland UDSK28-22MM-3/4"-F is a double cardan friction bearing universal joint with 22mm x 0.7500" bores, 6mm x 3/16" keyways, 1.745" (44.3mm) OD, 7.750" (196.9mm) length, and 5/16-18 set screws. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UDSK28-22MM-3/4"-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT28/44-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Keyway (K1) 6 mm Keyway (K2) 3/16 in B1 Max Shaft Penetration 1.610 in (40.9 mm) B2 Max Shaft Penetration 1.610 in (40.9 mm) Joint Outer Diameter (OD) 1.745 in (44.3 mm) Bore Tolerance +0.0010 in / -0.0000 in (+0.025 mm) Length (L) 7.750 in (196.9 mm) Center Yoke Length (LC) 2.750 in (69.9 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Product Specifications			
B1 Max Shaft Penetration Joint Outer Diameter (OD) 1.745 in (44.3 mm) Bore Tolerance 1.610 in (40.9 mm) 1.745 in (44.3 mm) Center Yoke Length (LC) 2.750 in (69.9 mm) Length (L) 7.750 in (196.9 mm) Center Yoke Length (LC) 2.750 in (69.9 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 California to cause cancer and birth defects or other reproductive harm. For more information go to	Bore (B1)	22 mm	Small Bore (B2)	0.7500 in
Joint Outer Diameter (OD) 1.745 in (44.3 mm) Bore Tolerance +0.0010 in / -0.0000 in (+0.025 in / -0.000 mm) 7.750 in (196.9 mm) Center Yoke Length (LC) 2.750 in (69.9 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Keyway (K1)	6 mm	Keyway (K2)	3/16 in
/ -0.000 mm) Length (L) 7.750 in (196.9 mm) Center Yoke Length (LC) 2.750 in (69.9 mm) Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application ↑ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	B1 Max Shaft Penetration	1.610 in (40.9 mm)	B2 Max Shaft Penetration	1.610 in (40.9 mm)
Yoke Length (LY) 2.500 in (63.5 mm) Hub Depth (LH) 1.610 in (40.9 mm) Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 MARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Joint Outer Diameter (OD)	1.745 in (44.3 mm)	Bore Tolerance	+0.0010 in / -0.0000 in (+0.025 mm / -0.000 mm)
Broached Set Screw 5/16-18 Screw Finish Black Oxide Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 ANARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Length (L)	7.750 in (196.9 mm)	Center Yoke Length (LC)	2.750 in (69.9 mm)
Peak Torque 13,050 in-lb (1,474.5 Nm) Rated Torque 2,610 in-lb (294.9 Nm) Max Operating Angle 90° Material Specification Alloy Steel Manufacturer Belden Universal Country of Origin USA Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Yoke Length (LY)	2.500 in (63.5 mm)	Hub Depth (LH)	1.610 in (40.9 mm)
Max Operating Angle90°Material SpecificationAlloy SteelManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC63452932693Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Broached Set Screw	5/16-18	Screw Finish	Black Oxide
ManufacturerBelden UniversalCountry of OriginUSARecommended LubricantLUBRIPLATE No. 1200-2Matching Boot CoverUBOOT28/44-NI-KITUPC63452932693Tariff Code8483.60.4000UNSPC25173810Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicationProp 65▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Peak Torque	13,050 in-lb (1,474.5 Nm)	Rated Torque	2,610 in-lb (294.9 Nm)
Recommended Lubricant LUBRIPLATE No. 1200-2 Matching Boot Cover UBOOT28/44-NI-KIT Tariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Max Operating Angle	90°	Material Specification	Alloy Steel
UPC 63452932693 Tariff Code 8483.60.4000 UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65	Manufacturer	Belden Universal	Country of Origin	USA
UNSPC 25173810 Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 △WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT28/44-NI-KIT
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application Prop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	UPC	63452932693	Tariff Code	8483.60.4000
Prop 65 AWARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	UNSPC	25173810		
California to cause cancer and birth defects or other reproductive harm. For more information go to	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	California to cause cancer and birth defects or other reproductive harm. For more information go to		