	т Q т т		7		
4			4		
ယ		LAYOUT SHOWN AS EXAMPLE	3		
	Keying Shown as example				
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
	Shell Material: AluminiumØS29.4 Max-Shell Plating: Black Zinc NickelZ31 Max-Insulator: ThermoplasticVV THREADM18x1-6g-Contacts: Copper Alloy: Second	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	CountryJurisdiction & Control ListFRNot Listed	2		
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D513Z04PC			
	-Temperature Range -65°C to +175°C	A 19-10-2016 First Release	_		
_	-Salt Spray : 500 hours -Mass : 21.04 g ± 10%	ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING			
		TITLE Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 13 Z 04 P C SHELL TYPE : Plug with RFI Shielding - - 13 Z 04 P C	SCALE General linear NPRDS / PROJECT NA Image: transmission of transmissi of transmission of transmission of transmission of transmission	1		
	CONTACT TYPE : Standard Crimp Contact				
	SHELL SIZE : 13 CONTACT TYPE : PIN(500 Ma PLATING : Z = Black Zinc Nickel CONTACT LAYOUT :		_		
	PLATING : Z = Black Zinc Nickel CONTACT LAYOUT :	13-04 FORMAT SOURIAU DRG N° SHEET A3 8D513Z04PC-C 1/2			
	H G F E	D C B A			

ſ	Ŧ	۵	וד	m	U	0	
		Contact Layout					
4	×	$ \begin{array}{c} $					
		+.000 (0.00) +.150 (0.81) +.146 (3.71) +.035 (0.89) +.000 (0.00) 083 (2.11) 146 (3.71) +.035 (0.89)					
۵							
	-					SOURIAU shall not be lial due to a use of the Pro the Specifications issued by (professional reco	oducts wl y either o
N						PN: 81	Counti FR
					A 19-10-20 ISS DATE Designed By:	16 First Release	
					TITLE	Gener	Alumir
→					SOURIA		rances: ± RIAU.C
					FORMAT A3		IRIAU 513Z
L	Н	G	F	E	D	С	

