


LDEEC2390KA5N00

Aliases (DEEC2390KA5N00)

LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.039 uF, 10%, 63 VAC, 100 VDC, 125°C, 1812, 1.7mm



Click here for the 3D model.

Dimensions	
Chip Size	1812
L	4.7mm +0.3/-0.2mm
W	3.3mm +/-0.3mm
Т	1.7mm MAX
В	0.4mm +0.5/-0.3mm

Packaging Specifications		
Packaging	T&R	
Packaging Quantity	4000	

General Information	,
Series	LDE
Dielectric	Metallized PEN Stacked
Style	SMD Chip
Features	Automotive Grade
RoHS	Yes
Qualifications	AEC-Q200
AEC-Q200	Yes
Shelf Life	104 Weeks
MSL	3

Specifications	
Capacitance	0.039 uF
Capacitance Tolerance	10%
Voltage AC	63 VAC
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Rated Temperature	125°C
Dissipation Factor	0.8% 1kHz
Insulation Resistance	1GOhms
Max dV/dt	100 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.