

Contact insert - HC-HV10-I-CT-F - 1405265

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON socket insert, for 830 V (III/3), with 10 N/O contacts and 2 switch contacts, crimp connection

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	85389099
Country of origin	China

Technical data

General

Note	For HEAVYCON-ADVANCE housing of B24 type and HEAVYCON housing of HV10 type, crimp contacts CK 2,5-ED (crimp contacts not included in scope of supply)
Connection method	Crimp connection
Pollution degree	3
Surge voltage category	III
Number of positions	10+2+PE
No. of power contacts	10
No. of control contacts	2
Insertion/withdrawal cycles	≥ 500
Type	B24
Conductor cross section	0.5 mm ² ... 4 mm ² (power contacts) 0.5 mm ² ... 4 mm ² (control contacts)
Connection cross section AWG	20 ... 12 (power contacts) 20 ... 12 (control contacts)

Contact insert - HC-HV10-I-CT-F - 1405265

Technical data

General

Stripping length of the individual wire	7.5 mm (Power contact)
	7.5 mm (control contact)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
---------------------------------	--

Material data

Inflammability class according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	830 V (power contacts)
	500 V (control contacts)
Rated surge voltage	8 kV (power contacts)
	6 kV (control contacts)
Rated current	25 A (power contacts)
	16 A (control contacts)

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424

ETIM

ETIM 5.0	EC000438
----------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Contact insert - HC-HV10-I-CT-F - 1405265

Approvals

Approvals submitted

Approval details


EAC

Drawings

Diagram

Dimensional drawing


Derating diagram



Dimensional drawing

Contact insert - HC-HV10-I-CT-F - 1405265

Schematic diagram



View termination side