T	—		0	D			
A Z ØS							
			LAYOUT SI	HOWN AS EXAMPLE			
	Keying Shown as example						
CHARACTERISTICS	Connector dimension	7					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal						
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer					ction & Control List		
 Contact Plating : Gold over copper Alloy 0.8μm minimum 		[FR Not Listed				
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511F02SNL				
-Temperature Range _: -65°C to +200°C		A 1	5-10-2016 First Release				
-Salt Spray : 48 hours							
		ISS Designed	DATE Latest modification - by By: Date:		CUSTOMER DRAWING	MOD N°	
		Т	TITLE Aluminium Plug 8D series				
	02 S N L	SCALE		eral linear lerances:	NPRDS / PROJECT 859		
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact			Cts IVA Image: Cts This document is the property			rty of	
SHELL SIZE : 11	500 Matings)	- SOURIAU WWW.SOURIAU.COW it must not be reproduced or					
PLATING : F = Nickel	CONTACT LA		SO	URIAU DRG N°		SHEET	
		A3		511F02SNL-C		1/2	
H G	F E	D	C	В	A		

r	Ŧ	ര	т	m	D	0
		Contact Layout				
4	.x .0 (2)	+Y IB IA + + + + + + + + + + + + +				
	Cont positi ID A B Sheli Arrangement size no. 11 -2	X-axis Y-axis (mm) (mm) + .095 (2.41) +.000 (.00) 095 (2.41) +.000 (.00)				
ယ						
	+					SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
N						PN: 8D511
					A 15-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
_					SCALE NA	Alum General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIA 8D511F
L	Н	G	F	E	D	С

