



SAW Components

SAW Duplexer for Femtocell and Small-cell

Band 12 (3G/LTE)

Series/type: B8012
Ordering code: B39741B8012P810

Date: July 09, 2014
Version: 2.0


© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


DataSheet

Application


- Low-loss SAW duplexer for 3G/LTE femtocell and smallcell systems (Band 12)
- Low insertion attenuation
- Low amplitude ripple
- Usable passband 17 MHz
- High power durability
- Rx = Uplink = 699-716 MHz
- Tx = Downlink = 729-746 MHz


Features

- Package size 2.5 * 2.0 mm²
- max. Package height 0.5 mm
- RoHS compatible
- Package for **Surface Mount Technology (SMT)**
- Ni, Au-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- Moisture Sensitivity Level 3


Pin configuration

- 3 RX output
- 1 TX input
- 6 Antenna
- 2, 4, 5, 7, 8, 9 To be grounded



DataSheet

Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω 17 nH
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics ANT - RX		min.	typ. @ 25 °C	max.	
Center frequency	f _C	—	707.5	—	MHz
Maximum insertion attenuation	α _{max}				
699.0 ... 714.75 MHz		—	2.3	3.0	dB
714.75 ... 716.0 MHz		—	2.4	4.5	dB
Amplitude ripple (p-p)	Δα				
699.0 ... 714.75 MHz		—	0.9	2.0	dB
699.0 ... 716.0 MHz		—	1.0	3.0	dB
Error Vector Magnitude	EVM ¹⁾				
@f _{carrier} 701.5 ... 713.5 MHz		-	2.2	5.0	%
Input VSWR (ANT port)					
699.0 ... 716.0 MHz		—	1.8	2.2	
Output VSWR (RX port)					
699.0 ... 716.0 MHz		—	2.0	2.3	
Attenuation	α				
100.0 ... 600.0 MHz		45	58	—	dB
693.25 ... 694.0 MHz		12	15	—	dB
694.0 ... 694.5 MHz		5	23	—	dB
694.5 ... 697.75 MHz		1.5	2.5	—	dB
716.0 ... 721.0 MHz		1	2.3	—	dB
721.0 ... 722.5 MHz		5	13	—	dB
722.5 ... 728.0 MHz		10	19	—	dB
729.0 ... 746.0 MHz		45	50	—	dB
746.0 ... 756.0 MHz		42	48	—	dB
758.0 ... 768.0 MHz		45	49	—	dB
777.0 ... 787.0 MHz		45	50	—	dB
788.0 ... 798.0 MHz		45	52	—	dB
869.0 ... 894.0 MHz		45	54	—	dB
1398.0 ... 1432.0 MHz		45	56	—	dB
1574.0 ... 1606.0 MHz		45	54	—	dB

Characterisitcs ANT - RX	min.	typ. @ 25 °C	max.	
1710.0 ... 1755.0 MHz	45	53	—	dB
1850.0 ... 1915.0 MHz	40	51	—	dB
1930.0 ... 1995.0 MHz	40	50	—	dB
2110.0 ... 2170.0 MHz	30	44	—	dB
2400.0 ... 2500.0 MHz	40	50	—	dB

1) Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

DataSheet

Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω 17 nH
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics TX - ANT		min.	typ. @ 25 °C	max.	
Center frequency	f _C	—	737.5	—	MHz
Maximum insertion attenuation 729.0 ... 746.0 MHz	α _{max}	—	1.8	2.5	dB
Amplitude ripple (p-p) 729.0 ... 746.0 MHz	Δα	—	0.6	1.3	dB
Error Vector Magnitude @f _{carrier} 731.5 ... 743.5 MHz	EVM ¹⁾	-	2.5	4.0	%
Input VSWR (TX port) 729.0 ... 746.0 MHz		—	1.8	2.0	
Output VSWR (ANT port) 729.0 ... 746.0 MHz		—	1.6	2.0	
Attenuation	α				
10.0 ... 699.0 MHz		30	42	—	dB
699.0 ... 716.0 MHz		45	51	—	dB
777.0 ... 787.0 MHz		35	48	—	dB
788.0 ... 798.0 MHz		35	45	—	dB
824.0 ... 849.0 MHz		35	41	—	dB
869.0 ... 894.0 MHz		35	40	—	dB
1398.0 ... 1432.0 MHz		35	45	—	dB
1458.0 ... 1492.0 MHz		35	46	—	dB
1574.0 ... 1606.0 MHz		35	47	—	dB
1710.0 ... 1755.0 MHz		35	49	—	dB
1850.0 ... 1915.0 MHz		40	49	—	dB
1930.0 ... 1995.0 MHz		40	49	—	dB
2097.0 ... 2148.0 MHz		30	46	—	dB
2110.0 ... 2170.0 MHz		30	46	—	dB
2187.0 ... 2238.0 MHz		30	44	—	dB
2400.0 ... 2500.0 MHz		35	42	—	dB

¹⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

DataSheet

Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω 17 nH
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics TX-RX				min.	typ. @ 25 °C	max.	
Attenuation							
	699.0 ... 716.0 MHz	α		48	52	—	dB
	729.0 ... 746.0 MHz			48	52	—	dB


Maximum Ratings

Storage temperature range	T _{stg}	-40/+85	°C	machine model, 1 pulse source and load impedance 50 Ω LTE 5 MHz downlink } average power T = 55°C, 50.000 h
DC voltage	V _{DC}	0	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	
Input power at pin 1				
729.0 ...746.0 MHz	P _{in}	31	dBm	
elsewhere	P _{in}	10	dBm	


¹⁾ According to JESD22-A115A (machine model), 1 negative and 1 positive pulses.



Frequency Response ANT-RX




Frequency Response ANT-RX






Frequency Response TX-ANT




Frequency Response TX-ANT






Frequency Response TX-RX





Frequency Response TX-RX









S11 VSWR (RX)



S22 VSWR (ANT)




S33 VSWR (TX)




DataSheet



EVM RX



EVM TX



SAW Components
B8012
SAW Duplexer
707.5 / 737.5 MHz

DataSheet



References

Type	B8012
Ordering code	B39741B8012P810
Marking and package	C61157-A3-A27
Packaging	F61074-V8232-Z000
Date codes	L_1126
S-parameters	B8012_NB.s3p, B8012_WB.s3p See file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8 th , 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2014. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, TFAP, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.