ATGBICS CWDM-SFP-2.5G-1470-120 Cisco Compatible Transceiver CWDM SFP 2.5G (120km, SMF, LC, 1470nm)

Brand : ATGBICS **Product code:** CWDM-SFP-2.5G-1470-120-C

Product name : CWDM-SFP-2.5G-1470-120 Cisco Compatible Transceiver CWDM SFP 2.5G (120km, SMF, LC, 1470nm)

0 Cisco



CWDM-SFP-2.5G-1470-120 Cisco Compatible Transceiver CWDM SFP 2.5G (120km, SMF, LC, 1470nm)

ATGBICS CWDM-SFP-2.5G-1470-120 Cisco Compatible Transceiver CWDM SFP 2.5G (120km, SMF, LC, 1470nm):

ATGBICS CWDM-SFP-2.5G-1470-120 2.5GBase CWDM supports a distance of up to 120km over single mode fibre (SMF) using a wavelength of 1470nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoCWDM-SFP-2.5G-1470-120= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 2500 Mbit/s Interface type * SFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector LC SFP transceiver standard CWDM	2500 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	imum transfer distance velength velength 1470 nm velength Division tiplexing (CWDM) ernet LAN ernet interface type 2.5 Gigabit Ethernet ital Diagnostics Monitoring	Operational conditions	
Maximum transfer distance Wavelength Coarse Wavelength Division Multiplexing (CWDM) Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
(DDM)		Width	13.4 mm
Features Product colour Housing material	Silver Metal	Depth Height Weight	56.5 mm 8.5 mm 15 g
Plug and Play Hot-swap Easy to install Country of origin Brand compatibility Cisco	✓	Packaging data	
	*	Number of products included Package type	1 pc(s) Box
	•	Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468714602

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.