

## Specification Sheet

Part Number: 166-90506

External NPT thread provides a secure connection.

Twist-on installation makes future access fast and easy.

Internal spigot design helps ease threading of fitting onto conduit.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.



HelaGuard Non-Metallic IP65 Compression Fitting, Straight, NPT Thread, 2.0" Dia., Black, 1/pkg

**Article Number** 166-90506

**Type** PSR200-S-2000

**Color** Black (BK)

**Quantity Per** pack

**Product Description** Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing.

<b>Short Description</b>	HelaGuard Non-Metallic IP65 Compression Fitting, Straight, NPT Thread, 2.0" Dia., Black, 1/pkg
<b>Global Part Name</b>	PSR200-S-2000-PA66-BK
<b>Length L (Imperial)</b>	2.2
<b>Length L (Metric)</b>	56.0
<b>Outside Diameter OD (Imperial)</b>	2.99
<b>Outside Diameter OD (Metric)</b>	76.0
<b>Nominal Diameter (Imperial)</b>	2.5
<b>Nominal Diameter (Metric)</b>	63
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Operating Temperature</b>	-40°F to +248°F (-40°C to +120°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1

**Package Quantity (Metric)** 1

**Customs Number** 3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)