



## IP66 Compact Unit LCS 75/ 5

terminal block, 5 pole, housing hole diameter: M25, voltage rating: 400 V, current rating: 16 A, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

reference number (ref.no.)	526205
PU	500
EAN	4028012137367

### Type

type	terminal block
number of poles	5 pole
clamping units per pole	extern: 1 / intern: 2
colour	grey
cross-section rating	2.5 mm <sup>2</sup>
connection type	screwless
PE function	yes

### Technical Data

voltage rating	400 V
current rating	16 A
impulse voltage rating	2.5 kV
insulating material	PA
contact material	Spring Steel, Copper
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
max. ambient temperature operation	40 °C
IP code	IP66
dismantling length PE	69.0 mm
dismantling length	60.0 mm
cable diameter min.	9.0 mm
cable diameter max.	13.5 mm
wall thickness min.	0.5 mm
wall thickness max.	2.5 mm
housing hole diameter	M25
internal stripping length	12.0 mm
external stripping length	17.0 mm

<b>tightening torque lock nut</b>	1,0 Nm
<b>tightening torque support sleeve</b>	1,0 Nm
<b>type of conductor solid external</b>	yes
<b>type of conductor flexibel external</b>	yes
<b>type of conductor stranded external</b>	yes
<b>type of conductor solid internal</b>	yes
<b>type of conductor stranded internal</b>	yes
<b>ammonia resistance</b>	yes

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
-------------------------	------------------------------

## Accessories

<b>ABK 75/ 5</b>	526206
------------------	--------