

FSP400-50UCB

FEATURES

- Certified CB 62368-1 & CB 60950-1
- Meet 80 Plus Bronze
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Over Current Protection
- Over Voltage Protection



SAFETY STANDARD APPROVAL



DESCRIPTION

FSP400-50UCB is a standard 1U form factor switching power supply. The power supply comes to offer the total power capacity up to 400 Watts, which makes it to be perfectly used in an industrial environment. In addition, the power supply is ideally the best choice for IPC controller, workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

GENERAL SPECIFICATIONS

Dimension (L x W x H):	190 x 100 x 40.5 (mm) 7.49 x 3.94 x 1.6 (inch)	Environment	Working temperature: 0°C to 50°C Storage temperature: -20°C to + 80°C Working humidity: 85% RH non-condensing Storage humidity: 95% RH non-condensing
Efficiency:	80 Plus Bronze	MTBF:	100,000 hours of continuous operation at 25°C, Max,-output load
Hold-up time at 100% Loading:	115V / 60Hz: ≥ 10ms 230V / 50Hz: ≥ 12ms	Applications:	Workstation ,Storage System ,IPC Controller
Operating altitude:	5,000 meters above sea level		

INPUT SPECIFICATIONS

Input voltage:	90-264Vac
Input frequency:	47-63Hz
Input current:	115Vac @ 6A, 230Vac @ 3A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb	-5V*
Max.	14.0A	16.0A	33.0A	0.3A	3.0A	0.1A
Min.	0.0A	0.0A	0.05A	0.0A	0.0A	0.0A
Regulation	±5%	±5%	±5%	±10%	±5%	±10%
Ripple/Noise	50 mV	50 mV	120 mV	120 mV	50 mV	100 mV

The +3.3V and +5V total output shall not exceed 90W

* -5V is optional

MECHANICAL SPECIFICATIONS

UNIT: mm [inch]

