

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GQM22M5C2H100JB01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

41.0mg

http://www.murata.com/en-us/products/productdetail?partno=GQM22M5C2H100JB01%23

References

Specifications

180Embossed Tape

330Embossed Tape

Packaging

Mass (typ.)

1 piece

L

Κ

GQM22M5C2H100JB01K




< List of part numbers with package codes > GQM22M5C2H100JB01L GQM22M5C2H100JB01K

Applications

| Unsuitable | Please be sure to read and comply with | |
|--------------|-------------------------------------------|--|
| Applications | these "Precautions for use." | |
| | | |
| | Products after confirming the | |
| | | |
| | performance and reliability of the actual | |
| | Product. | |

Appearance & Shape





1 of 2

Standard

Packing Quantity

1000

4000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GQM22M5C2H100JB01K

Note: This datasheet may be out of date. Please download the latest datasheet of GQM22M5C2H100JB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GQM22M5C2H100JB01%23

"#" indicates a package specification code.



Specifications

| Length | 2.8±0.5mm |
|----------------------------------------------------|--------------|
| Width | 2.8±0.4mm |
| Thickness | 1.15±0.2mm |
| Capacitance | 10pF ±5% |
| Distance between external terminals g | 1.0mm min. |
| External terminal size e | 0.3mm min. |
| Operating Temperature Range | -55℃ to 125℃ |
| Rated Voltage | 500Vdc |
| Size code in inch(mm) | 1111 (2828M) |
| TC | 0±30ppm/°C |
| Temperature characteristics (complied standard) | C0G(EIA) |
| Temperature range of temperature characteristics | 25℃ to 125℃ |

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

