

PL519M Series 5mm LED Snap-in Panel Mount Holder

Features

- *Snap-in Design Requires no Hardware
- *Mounting Hole 7.2 mm (0.287")
- *Housing Material Black Nylon UL94V-2
- *1 Three Leaded Bi-Color Hi-Eff Red/Green LED with White Diffused Lens used
- *26AWG 6" (+) Red and Green (-) Black Wire Leads
- *Common Cathode
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100µA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25 °C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
6" Wire Leads			nm	nm	Deg				
PL519M-1RG1213-2	Orange-Red Green	GaAsP GaP	635 567	626 572	70°	2.1	2.6	14.0 14.0	35.0 34.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

