

## ATGBICS S-RJ01-C network transceiver module Copper 1250 Mbit/s SFP

Brand : ATGBICS

Product code: S-RJ01-C

Product name : S-RJ01-C

Mikro Tik Compatible Transceiver SFP 10/100/1000Base-T Copper RJ45 Connector 100m

ATGBICS S-RJ01-C network transceiver module Copper 1250 Mbit/s SFP:

ATGBICS S-RI01 SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. Mikro Tik 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product is built to the exact specification of Mikro Tik S-RJ01= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS S-RJ01-C. SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Features	
SFP transceiver type *CopperMaximum data transfer rate *1250 Mbit/sInterface type *SFPSingle-mode fiber (SMF) supportedXMulti-mode fiber (MMF) supportedXSFP transceiver standardTXMaximum transfer distance100 mEthernet LAN✓Copper ethernet cabling technology10BASE-T,100BASE-TX,1000BASE-TXAuto MDI/MDI-X✓Digital Diagnostics Monitoring (DDM)X	1250 Mbit/s SFP X TX	Brand compatibility	MikroTik
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
	Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%	
Features		Weight & dimensions	
Product colour Housing material Plug and Play	rolour Silver material Metal Play I support I nstall I of origin United Kingdom	Width Depth Height Weight	13.4 mm 56.6 mm 8.5 mm 24 g
Hot-Plug support Hot-swap		Packaging data	
Easy to install Country of origin		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.