3 CONTACTS BLUE MALE HOUSING (ONLY FOR BOARD MOUNT CONTACTS)

	11.80	
. 15.50		
	3 1	


TOLERANCE UNLESS OTHERWISE SPECIFIED		
.X	±0.38	
VV	10.25	

.XXX ±0.13


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER **ORIGINAL**







NOTE:

ELECTRICAL SPECIFICATIONS:

VOLTAGE RATING: 250V MAX. **CURRENT RATING:** 3A per CONTACT **CONTACT RESISTANCE:** 15mΩ MAX. **INSULATOR RESISTANCE:** $1000M\Omega$ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS) **OPERATING TEMPERATURE:** -40°C ~ 105°C

MATERIAL & FINISH:

HOUSING: PBT WITH GLASS, UL94V-0 CONTACTS: BRASS, TIN PLATED SEALS: SILICONE RUBBER

560 SERIES WATERPROOF CONNECTOR



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	ACAD REFERENCE NO.: 560 Assembly				
	DRAWN: C.B	DATE: July 23, 2020			
	CHECKED:	DATE:			
	SCALE: 2:1	SHEET 1 OF 1			
ĺ	DRAMING AND FOR A				

ISSUE DRAWING NUMBER: 560 Assembly PART NUMBER: 560-003-420-301