



Click here for the 3D model.

0402
1mm +/-0.05mm
0.5mm +/-0.05mm
0.5mm +/-0.05mm
0.25mm +/-0.1mm
0.25mm +/-0.1mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	10000

General Information			
Series	L-RMS		
Style	SMD Chip		
Description	Surface Mount Inductor		
RoHS	Yes		
Core	Ceramic		
Winding Type	Multilayer		
Notes	Suggested Replacement - https://productfinder.pulseelectronics.com/part/BSCH0010050533NJCS.		

Specifications	
Inductance	0.033 uH
Inductance Tolerance	5%
Temperature Range	-55/+125°C
Current	200 mAmps (MAX)
DC Resistance	0.8 Ohms
Quality Factor	11 at 100 MHz, 20 at 500 MHz, 23 at 800 MHz, 22 at 1000 MHz
Self-Resonant Frequency	1300 MHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.