



NON-CONTACT SAFETY SWITCHES



RE300-DA03P | RE300

NON-CONTACT SAFETY SWITCHES

Ordering information



Туре	Part no.
RE300-DA03P	6025080

Other models and accessories → www.sick.com/RE300



Detailed technical data

Features	
System part	Sensor with actuator
Sensor principle	Magnetic
Number of N/O contacts	1
Number of N/C contacts	1
Safe switch on distance \mathbf{S}_{ao}	5 mm
Safe switch off distance S _{ar}	15 mm
Active sensor surfaces	2
Actuation directions	5

Safety-related parameters

B _{10d} parameter	2×10^7 switching cycles (with small load)
Туре	Type 4 (EN ISO 14119)
Actuator coding level	Low coding level (EN ISO 14119)
Safe state in the event of a fault	The switch has no internal fault detection and is unable to assume a safe state in the event of a fault. Fault detection is performed by the connected safety-related logic unit.

Functions

Safe series connection	None, only individual wiring (with diagnostics)
Interfaces	
Connection type	Cable
Length of cable	3 m
Cable material	PVC
Electrical data	
Type of output	Reed contacts
Switching voltage	≤ 30 V DC
Switching current	≤ 30 mA
Mechanical data	
Design	Rectangular
Dimensions (W x H x D)	19 mm x 82 mm x 19 mm
Weight	+ 0.168 kg


RE300-DA03P | RE300

NON-CONTACT SAFETY SWITCHES

Housing material	ABS shape
Ambient data	
Enclosure rating	IP67
Ambient operating temperature	-10 °C +55 °C
Storage temperature	-25 °C +70 °C
Vibration resistance	10 Hz 55 Hz, 0.35 mm (IEC 60068-2-6)
Shock resistance	30 g (IEC 60068-2-29)
Classifications	
eCl@ss 5.0	27272402
eCl@ss 5.1.4	27272402
eCl@ss 6.0	27272402
eCl@ss 6.2	27272402
eCl@ss 7.0	27272402
eCl@ss 8.0	27272402
eCl@ss 8.1	27272402
eCl@ss 9.0	27272402
eCl@ss 10.0	27272402
eCl@ss 11.0	27272402
eCl@ss 12.0	27274401
ETIM 5.0	EC002544
ETIM 6.0	EC002544
ETIM 7.0	EC002544
ETIM 8.0	EC002544
UNSPSC 16.0901	39122205

Dimensional drawing (Dimensions in mm (inch))


Actuator




RE300-DA03P | RE300

NON-CONTACT SAFETY SWITCHES


Sensor



Response range




Pin assignment



1 BU	NO contact	
4 RE	NO contact	
2 YE	NC contact	
3 GN		

Sensor timing



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

