



| ELECTRICAL | MECHANICAL | ENVIRONMENTAL | HOUSING | MATERIAL | FINISH |
|---|--|--|--|--|-------------------------------|
| Nominal Impedance (Ohms) <u>50</u> | Interface Dimensions MIL-STD-348A, Fig. 310-2 | Temperature Rating <u>-65°C TO +165°C</u> | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 | GOLD PLATE PER MIL-G-45204 | |
| Frequency Range (GHz) DC to <u>18</u> | Mating Characteristics: | Vibration MIL-STD-202, Method 204, Condition D | DIELECTRIC | PTFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| Volt Rating (VRMS MAX) @ Sea Level <u>500</u> | Insertion (MAX Lbs) <u>2.0</u> | Shock MIL-STD-202, Method 213, Condition I | CENTER CONTACT | BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 |
| VSWR <u>1.05 +0.008 f(GHz)</u> | Withdrawal (MIN Oz) <u>1.0</u> | Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +115°C | COMPONENT | | |
| Insertion Loss (dB MAX) <u>.03 x √f(GHz)</u> | Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u> | Moisture Resistance MIL-STD-202, Method 106. No Measurements at At High Humidity. I.R. Shall Be At Least 200 Megaohms Within 5 Minutes After Removal From Humidity. | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | DRAWN BY <u>PATLAN</u> DATE <u>2/12/98</u> | |
| Corona, 70,000 Ft (VRMS MIN) <u>375</u> | Center Contact Captivation | Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray | FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1° | CHECKED BY _____ | |
| Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1500</u> | Axial (Lbs) <u>N/A</u> | | | APPD BY <i>Patlan</i> DATE <u>4/3/98</u> | |
| Contact Resistance (Milliohms MAX) | Radial (In-Oz) <u>N/A</u> | | | M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577 | |
| Center Contact <u>3.0</u> | Cable Retention | | | USE ASS'Y PROCEDURE | |
| Outer Contact <u>2.0</u> | Axial Force (Lbs) <u>30</u> | | | 408-04838 (20-553) | |
| Cable to Housing <u>0.5</u> | Torque (In-Oz) <u>16</u> | | | NO. AP. _____ | |
| RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>1,000</u> | Weight (Grams) <u>TBD</u> | | | TITLE OSM FLANGE MOUNT JACK DIRECT SOLDER ATTACHMENT M39012/82-3001 CAT B | |
| I.R.(Megohms MIN) <u>5,000</u> | .XXX = in XX.X = mm (REF) | | | SIZE <u>B</u> | CODE IDENT NO. <u>26805</u> |
| | | | | 2006-8001-90 | |
| | | | | SCALE <u>5 : 1</u> | REV <u>010</u> |
| | | | | SHEET 1 OF 1 | |