


# Fiber optic - HS LC-H-D2/ R2XC4-2,54 - 2202531


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Light guides, passive, rigid, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)



## Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 055626 149134
GTIN	4055626149134

## Technical data

### Product properties

Brief article description	Fiber optic
Type	HS LC-H-D2/ R2XC4-2,54
Order No.	2202531
Type	passive, rigid
Alignment	Horizontal
Head form	Round, conical

### Dimensions

Pitch	2.54 mm
Diameter	2 mm

### Material specifications

Material	PC
Color (RAL)	transparent
	black

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

# Fiber optic - HS LC-H-D2/ R2XC4-2,54 - 2202531

## Technical data

### General information

Type of note	Assembly instruction:
Note	Refer to the data sheet for the range in the download area.
	To prevent glare, the system has an aperture. This also makes mixed colors possible.

### Packaging details

Pieces per package	100
Denomination packing units	Pcs.

### Standards and Regulations

Flammability rating according to UL 94	HB
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>