Keying Shown as example	LAYOUT SHOWN AS EXAMPLE
-Standard : Based on MIL-DTL-38999 Series III       Dim       Nominal         -Shell Material       : Aluminium       ØS       35.7 Max         -Shell Plating       : Black Zinc Nickel       Z       31 Max         -Insulator       : Thermoplastic       VV THREAD       M25x1-6g         -Contacts       : Copper Alloy       -Source Contacts       -Source Contacts	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
-Seals & Grommet       : Silicon Elastomer         -Contact Plating       : Gold over copper Alloy 0.8μm minimum         -Durability       : 500 Mating cycles         -Delivered without Souriau contacts	Country     Jurisdiction & Control List       FR     Not Listed   PN: 8D517Z06SNL
-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 29.9 g ± 10%	A       18-10-2016       First Release         ISS       DATE       Latest modification - by       MOD N°         Designed By:       Date:       CUSTOMER DRAWING
	TITLE     Aluminium Plug 8D series
BASIC SERIES:     8D     5     -     17     Z     06     S     N     L       SHELL TYPE     : Plug with RFI Shielding	SCALE     General linear     NPRDS / PROJECT       NA     Tolerances:     859       ±     This document is the property of source of sourc
CONTACT TYPE       : Standard Crimp Contact       ORIENTATION : N         SHELL SIZE : 17       CONTACT TYPE : SOCKET(500 Matings)         PLATING       : Z = Black Zinc Nickel       CONTACT LAYOUT : 17-06	SOURIAU     SOURIAU       FORMAT     SOURIAU DRG N°
H G F E	A3         8D517Z06SNL-C         1/2           D         C         B         A

r	т	۵	г –	m	Ū	0
		Contact Layout				
4		$ \begin{array}{c} \bullet^{+Y} \\ \bullet \\ $				
_	-× (	D⊕ F⊕ ⊕B +x Contacts (Insert arrangement 17-6)				
	Conta position A B C C D E	Location           X-axis         Y-axis           (mm)         (mm)           +.121 (3.07)         +.209 (5.31)           +241 (6.12)         +.000 (0.00)           -0.000 (0.00)        241 (6.12)           -241 (6.12)         +.000 (0.00)          121 (3.07)         +.209 (5.31)				
ω	size no. co	+.000 (0.00)         +.000 (0.00)           mber of ntacts         Size contacts         Service rating iocation         Contact iocation         Supersedes           6         12         I         All         MS20053-6				
	-				[	
	•					SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						PN: 8D5172
					A 18-10-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<b>_</b>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
				_	FORMAT A3	SOURIAU 8D517Z0
	Н	G	F	E	D	C

	σ		Þ	•		
						4
					1	3
any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)						
ntry R	Jurisd	liction & C Not List	Control List		J	2
	06SNL					2
		CUSTO	MER DRAWING		/OD N°	
inium Plug 8D series						
r	NPRDS / PROJECT					
			859		of	1
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	DRG N° SNL-C				SHEET 2/2	
	В		A			