Γ	т <u>0</u> т		0	Ξ	Þ	
4	Z D D D D D D D D D D D D D D D D D D D					4
ω			LAYOUT SHOWN AS EXA	AMPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
$ \longrightarrow $	-Standard : Based on MIL-DTL-38999 Series III ØS 35.7 Max					
N	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
	-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories		FR Not Listed 2 PN: 8D517Z22PD 2			2
	-Temperature Range : -65°C to +175°C	A 18-10-2016	First Release			
	-Salt Spray : 500 hours					
		ISS DATE Designed By:	Latest modification - by Date:	CUSTO	MOD N MER DRAWING	
		TITLE	TITLE Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 17 Z 22 P D SHELL TYPE : Plug with RFI Shielding - - 17 Z 22 P D	SCALE -	General linear Tolerances:	NPR	DS / PROJECT 859	-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : D	SOURIAU	WWW.SOURIAU.CO	DM _{it}	s document is the property of SOURIAU must not be reproduced or	
	SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings)	FORMAT			municated without permission SHEET	
	PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-22	A3	SOURIAU 8D517Z2		1/2	
I		,	0DJ1/77	270-6	1/2	

	Ŧ	۵	וד	m		0
4		Contact Layout 22				
 	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0				
						SOURIAU shall not be liable for a due to a use of the Products v the Specifications issued by either (professional recommend
N					A 18-10-20 ISS DATE	Coun FR PN: 8D517
					Designed By: TITLE SCALE NA	Date: Date: Alumi General linear Tolerances: ±
	Н	G	F	E	FORMAT A3	U WWW.SOURIAU. SOURIAU 8D5172 C

