

Available for these models with lower speed and same physical structure. All model may be followed by ARxx or AFxx series suffixes. This test report applies to PFB90x90x38 mm series as the right table	PFB0924UHE-F00	PFB0924GHE		
	PFB0924GHE-F00	PFB0924EHE		

Representative Test P/N :PFB0924DHE-F00	
Equipment: Oven :E24-F0059	

☉ **L₁₀ Expectancy: 70,000 hours minimum @ fan rated voltage and the temperature of 40°C**
 According to the equation for **Weibull distribution**, **MTTF ≐ 7×L10 = 490,000 hours**

And we rely on a zero failure Weibull test strategy and accelerated testing technique, to determine the total test time (t) for verifying the above life estimation by the equations,

$$t = 1.036 \times \text{MTTF} \times [(B_{r,c}) \div n]^{0.91} \div A_F, \text{ and } A_F = 2^{(T_s - T_u)/10}$$

where, (B_{r,c}) is Poisson distribution factor with the failure number of r equal to 0 and the decimal confidence level of c equal to 0.90(90%).

Stress/Elevated Temperature Ts (°C) (Actual Test Temperature)	Unstress Temperature Tu (°C)	Acceleration Factor A _F	Quantity of Test Devices n (pcs)	Poisson Distribution Factor B _{r,c}	Required test time with zero failure t (hours)	Actual test time with zero failure t (hours)	Verified MTTF 40 °C (hours)	Verified L ₁₀ 40 °C (hours)
60	40	4.00	56	2.303	6,956	13,956.0	983,161	140,452

Test Progress:

Date for Test Beginning	Date for Test Termination (at least)	Current Test Status			Current Total Test Time (hours)
2005/3/14 11:30 PM	2007/10/30 8:33 AM	<input type="checkbox"/> In process	<input checked="" type="checkbox"/> In process (exceed requested)	<input type="checkbox"/> Termination	13956.0

Herewith , we could assume as right on the basis of above test result. Besides, if the actual test time exceed the required, it comes out that those fans' L₁₀ expectancy and MTTF are greater than the warrant. (**MTTF** : means Mean Time To Failures, it should be used in a non-repairable system setting. Now we show the MTTF in our life report, that's because we will not repair the failed fans during life experiment. **MTBF**: means Mean Time Between failures, it should be used in a repairable system setting.)

Temperature for MTTF Estimation (°C)	Acceleration Factor A _F	Estimated MTTF (hours)	Estimated L ₁₀ (hours)
25	11.31	2,780,800	397,257
30	8.00	1,966,323	280,903
40	4.00	983,161	140,452
50	2.00	491,581	70,226
60	1.00	245,790	35,113

Fan permission criteria for the measurement after test :

1. For current, the limit is less than spec.(max.).
2. For speed, the allowable decrease is less than 15%.
3. For noise, the limit is less than spec.(max.). + 3 dB

Test Result	<input checked="" type="checkbox"/> Accept
	<input type="checkbox"/> Reject

QE File No.	Time-out for function test or others (hours)	Issued Date	Reported By	Approved By
DG05FNL050	16069.50	2008/8/17 1:00 AM	Nan Yang	Zenny Lei



DC FAN FUNCTION TEST RECORD FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure.
 All model may be followed by ARxx or AFxx series suffixes. This test report applies to PFB90x90x38 mm series as the right table

PFB0924UHE-F00	PFB0924GHE
PFB0924GHE-F00	PFB0924EHE

Required Test Time (hrs)	Date for Test Beginning	Date for Test Termination	Sample Size (pcs):	Failure (pcs):	Current Total Test Time (hrs)
6,956	2005/3/14 11:30 PM	2007/10/30 8:33 AM	56	0	13956.0

Representative Test P/N :PFB0924DHE-F00	Current Test Status	<input type="checkbox"/> In process	<input checked="" type="checkbox"/> In process (exceed requested)	<input type="checkbox"/> Termination
---	----------------------------	-------------------------------------	---	--------------------------------------

Equipment: Oven :E24-F0059

Test Data Between Initial Test and Final Test

Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)
	Current Spec. (A)	Current Spec. (A)		Speed Spec. (RPM)	Speed Spec. (RPM)		Noise Spec. (dB A)	Noise Spec. (dB A)	
	1.74Max.	1.74Max.		7360-8640	7360-8640		71.5Max	71.5Max	
1	1.43	1.46	2.0	8235	7800	-5.3	65.9	65.5	-0.6
2	1.42	1.45	1.9	8242	7900	-4.1	65.5	66.4	1.4
3	1.42	1.53	7.9	8247	8053	-2.4	65.1	65.6	0.8
4	1.43	1.41	-1.5	8229	7899	-4.0	65.7	65.4	-0.5
5	1.42	1.43	0.4	8245	8072	-2.1	65.4	66.1	1.1
6	1.45	1.47	1.4	8159	7909	-3.1	65.9	65.3	-0.9
7	1.45	1.42	-1.8	8174	8003	-2.1	65.2	65.6	0.6
8	1.50	1.44	-3.9	8282	7961	-3.9	65.8	66.2	0.6
9	1.43	1.41	-1.3	8221	7875	-4.2	65.1	65.9	1.2
10	1.52	1.43	-5.7	8224	7939	-3.5	66.3	65.8	-0.8
11	1.44	1.40	-2.7	8216	7809	-5.0	65.7	65.8	0.2
12	1.51	1.48	-2.3	8259	7953	-3.7	65.5	66.2	1.1
13	1.42	1.40	-1.4	8259	8082	-2.1	65.3	66.1	1.3
14	1.49	1.42	-4.4	8274	8017	-3.1	65.7	65.0	-1.1
15	1.41	1.51	6.8	8283	8114	-2.0	66.0	65.7	-0.5
16	1.50	1.53	1.9	8232	7970	-3.2	65.9	66.2	0.5
17	1.41	1.42	0.8	8269	8013	-3.1	65.3	65.7	0.6
18	1.51	1.44	-4.6	8232	7940	-3.5	65.9	65.9	0.0
19	1.52	1.51	-0.9	8231	7841	-4.7	66.0	66.1	0.2
20	1.40	1.43	1.8	8177	8036	-1.7	65.4	66.0	0.9
21	1.51	1.49	-1.4	8245	8016	-2.8	65.7	65.8	0.2
22	1.39	1.43	3.1	8210	7850	-4.4	65.9	65.7	-0.3
23	1.51	1.41	-7.0	8242	8024	-2.6	65.5	66.1	0.9
24	1.39	1.49	7.4	8181	7995	-2.3	65.8	65.4	-0.6
25	1.46	1.49	1.9	8104	7909	-2.4	65.9	66.1	0.3
26	1.55	1.38	-10.8	8093	7866	-2.8	65.7	65.6	-0.2
27	1.52	1.40	-8.1	7940	7861	-1.0	65.7	66.2	0.8
28	1.58	1.47	-7.2	8047	7889	-2.0	65.5	66.3	1.2
29	1.57	1.44	-8.2	8072	8046	-0.3	65.3	65.7	0.6
30	1.50	1.47	-2.1	8012	7970	-0.5	65.8	65.8	0.0
31	1.55	1.41	-9.1	8091	7967	-1.5	65.7	65.4	-0.5
32	1.49	1.49	-0.3	8003	7959	-0.5	65.3	66.0	1.1
33	1.55	1.47	-5.5	8073	7967	-1.3	65.9	66.3	0.6
34	1.52	1.42	-6.3	8104	7896	-2.6	66.2	65.7	-0.8
35	1.48	1.40	-5.5	8044	8158	1.4	65.7	65.5	-0.3

QE File No.	Time-out for function test or others (hours)	Issued Date	Reported By	Approved By
DG05FNL050	16069.50	2008/8/17 1:00 AM	Nan Yang	Zenny Lei



DC FAN FUNCTION TEST RECORD FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure.
All model may be followed by ARxx or AFxx series suffixes. This test report applies to PFB90x90x38 mm series as the right table

PFB0924UHE-F00	PFB0924GHE		
PFB0924GHE-F00	PFB0924EHE		

Required Test Time (hrs)	Date for Test Beginning	Date for Test Termination	Sample Size (pcs):	Failure (pcs):	Current Total Test Time (hrs)
6,956	2005/3/14 11:30 PM	2007/10/30 8:33 AM	56	0	13956.0

Representative Test P/N :PFB0924DHE-F00	Current Test Status	<input type="checkbox"/> In process	<input checked="" type="checkbox"/> In process (exceed requested)	<input type="checkbox"/> Termination
---	----------------------------	-------------------------------------	---	--------------------------------------

Equipment: Oven :E24-F0059

Test Data Between Initial Test and Final Test

Sample No.	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)	Initial Test	Final Test	Deviation (%)
	Current Spec. (A)	Current Spec. (A)		Speed Spec. (RPM)	Speed Spec. (RPM)		Noise Spec. (dB A)	Noise Spec. (dB A)	
	1.74Max.	1.74Max.		7360-8640	7360-8640		71.5Max	71.5Max	
36	1.53	1.45	-5.1	8101	7984	-1.4	65.5	66.1	0.9
37	1.46	1.50	2.7	8078	8121	0.5	65.9	65.9	0.0
38	1.54	1.46	-5.1	8078	7972	-1.3	65.7	65.7	0.0
39	1.57	1.47	-6.6	8109	7841	-3.3	65.4	66.2	1.2
40	1.52	1.46	-4.1	8103	7924	-2.2	66.2	66.0	-0.3
41	1.56	1.44	-7.6	8078	7883	-2.4	65.9	65.8	-0.2
42	1.54	1.41	-8.8	8074	7875	-2.5	65.8	66.3	0.8
43	1.57	1.48	-5.8	8074	7927	-1.8	65.5	66.1	0.9
44	1.52	1.40	-8.2	8104	7917	-2.3	65.3	65.9	0.9
45	1.56	1.41	-9.7	8093	7899	-2.4	65.7	66.1	0.6
46	1.51	1.45	-3.8	8091	7984	-1.3	65.4	65.7	0.5
47	1.54	1.47	-4.7	8120	8017	-1.3	65.5	66.3	1.2
48	1.53	1.50	-1.8	8062	7963	-1.2	65.9	65.9	0.0
49	1.54	1.44	-6.6	8120	7901	-2.7	65.3	66.0	1.1
50	1.52	1.47	-3.5	8074	8017	-0.7	66.1	65.5	-0.9
51	1.55	1.46	-5.9	8082	7939	-1.8	65.8	65.8	0.0
52	1.51	1.47	-3.0	8070	7915	-1.9	66.1	66.0	-0.2
53	1.55	1.49	-3.6	8070	7965	-1.3	65.4	66.1	1.1
54	1.52	1.42	-6.8	8052	8087	0.4	65.7	65.5	-0.3
55	1.60	1.38	-13.8	8027	7923	-1.3	65.3	65.7	0.6
56	1.60	1.46	-8.6	8017	8018	0.0	65.8	66.1	0.5
X-Bar	1.500	1.448	-	8139.8	7957.7	-	65.67	65.87	-
σ	0.057	0.037	-	88.238	79.480	-	0.289	0.300	-

QE File No.	Time-out for function test or others (hrs)	Issued Date	Reported By	Approved By
DG05FNL050	16069.50	2008/8/17 1:00 AM	Nan Yang	Zenny Lei