

Specifications & Requirement

Vaccine USB3	PN	ULD-VAU31A
	License	1 year
	Interface	USB1.1(Full Speed)/ USB 2.0(High Speed/Full Speed)
	Maximum current	Scanning: 220 mA Standby: 140 mA
	Operating environment	Temperature: 0 to 50°C Humidity: 30 - 80 % *non-condensing
	Certificates	VCCI Class B, CE, FCC
	Weight & Dimensions	11g L 79.0 mm x W 18.0 mm x H 9.4 mm (With a cover)
	Language	English *Depends on Windows Language(English)
Computers	Hardware	DOS/V computer with USB port Free memory: more than 512 MB (1GB is better)
	Settings	Page cash ON (recommended) CD-ROM drive recognition (recommended) CD-ROM Auto-run (recommended)
	OS	Windows 7, Windows 8, Windows 8.1, Windows 10, Windows Server 2008 (SP2), Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Embedded Standard 7, Windows Embedded POS Ready 7
	Permission requirement	Administrators, Restricted users
	Screen resolution	640 x 480 and more (Less than 800 x 600)

Status indicators

Blue LED	Red LED	Status
Flashing	Flashing	Scan in progress
On	Off	No viruses
Off	On	Detected viruses
Off	Flashing	Error

No Viruses



Detected Viruses



Where to buy

**HAGIWARA Solutions**

<https://www.digikey.com/en/supplier-centers/hagiwara-solutions>