




1








.XX ±0.13

.XXX ±0.05

## NOTES:

| MATERIAL:<br>HOUSING:<br>SHELL:<br>CONTACT:                 | THERMOPLASTIC POLYESTER, UL94V-0<br>STEEL, NICKEL PLATED<br>COPPER ALLOY, 30µ GOLD PLATED |
|---|---|
| OPERATING TEMPERATURE:                                      | -55°C ~ 125°C   |
| POWER/CO-AX CONTACT RATING:<br>(IF PRESENT)                 | 40A (CURRENT)   |
| SIGNAL CONTACT CURRENT RATING<br>SIGNAL CONTACT RESISTANCE: | : 5A PER CONTACT<br>10mΩ MAX.   |
| INSULATOR RESISTANCE:<br>DIELECTRIC                         | 5000MΩ min.   |
| WITHSTANDING VOLTAGE:                                       | 1000V AC rms  |

| COMBINATION D-SUB   |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|---|--|--------------------------------------|------------------|-------|
|   |  | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|   |  | CHECKED:                             | DATE:            |       |
| EDAGE EDAC INC<br>TORONTO, ONTARIO<br>CANADA<br>VOLID CONNECTION TO OLIAI ITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|   |  | DRAWING NUMBER: 630-7W2              | -640-4N2         | ISSUE |
|   |  | PART NUMBER: 630-7W2                 | -640-4N2         | 1     |



THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

ĦS

COMPLIANT

F

