1	т <u>G</u> т	т	D	0	σ	>	_
4							4
ω				LAYOUT SHOWN AS	EXAMPLE		3
	Keying Sho	own as example					
	CHARACTERISTICS	Connector dimension	1				
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max					
2	-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed				
	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			FR Not Listed 2 PN: 8D511W01SN 2			
	-Temperature Range _: -65°C to +175°C		A 17-10-20	016 First Release			
	-Salt Spray : 500 hours		ISS DATE			MOD N°	J°
	-Mass : 17.92 g ± 10%		Designed By:	Date:	CUST	OMER DRAWING	·
		TITLE	Aluminium Plug 8D series				
_	BASIC SERIES: 8D 5 - 11 W 01 S N SHELL TYPE : Plug with RFI Shielding		SCALE NA	General linear Tolerances:		RDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission			
	SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-02				U DRG N°	SHEET	
			A3		V01SN-C	1/2	
1				000111		1	1

r	Ξ	ര	гт —	m		0
		Contact Layout				
4		01				
		1#12				
	Ctc A	11-01 X Y 0 0				
ω						
	F					SOURIAU shall not be liable for an
						due to a use of the Products wh the Specifications issued by either o (professional recommendat
N						PN: 8D511V
					A 17-10-20 ISS DATE	16 First Release
					Designed By:	Date:
_					SCALE NA	General linear Tolerances: ±
					FORMAT A3	U WWW.SOURIAU.C SOURIAU 8D511W
l	Н	G	F	E	D	C

